

Product Specification

FUEL OIL CST 380

Fuel oil is a fraction obtained from petroleum distillation, either as a distillate or a residue.

QUALITY DATA

| Parameters | Method | Unit | Typical Result |
|--------------------------|--------------|---------|----------------|
| Color | ASTM D1500 | - | BLACK |
| Density @ 15°C | ASTM D1298 | Kg/L | 0.991 |
| Viscosity @ 40°C | ASTM D445 | cSt | 380 |
| Flash Point | ASTM D93 | °C | 66 |
| Pour Point | ASTM D97 | °C | -3 |
| Water Content | ASTM D95 | % Vol | Max 0.1 |
| Ash Content | ASTM D482-07 | % m | 0.15 |
| Sulfur Content | ASTM D4294 | % m | 3.5 |
| Vanadium | IP 470 | mg/kg | 77 |
| Zinc | IP 470 | mg/kg | Max 15 |
| Phosphorus | IP 470 | mg/kg | <1 |
| Calcium | IP 470 | mg/kg | 6 |
| Aluminum | IP 470 | mg/kg | <5 |
| Potential Total Sediment | IP 390 A | % (m/m) | 0.01 |

For Health & Safety information refer to the most current version of the product MSDS

The data contained herein is believed to be accurate at the time of distribution. However, ALPHINE OIL does not assume any legal liability whatsoever for the accuracy or completeness of the information contained herein. Users should undertake sufficient verification and testing to determine the suitability of this product for their own purposes.